



GU Bolt High Bay

120W-200W Adjustable Beam, Wattage & Colour

Technical

• Input Voltage	AC 200-240V
• Beam Spread	60°/90°/110°
• CRI	>70
• Power Factor	0.95
• Operating Temp.	-40 to +50°C
• Materials	Die-Cast Aluminium
• Lens Material	Polycarbonate
• IP Rating	IP65
• IK Rating	IK08
• Dimmable	1-10V
• Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
• Emergency Output	850Lm



GU Bolt Features



IP65 Ingress Protection



Wattage Switchable



1.5m Cable Flex



1-10V Dimmable (as standard)



Adjustable Beam 60°/90°/110°

Part Code: GU-BOLT-120/150/200TC/BA

Power	Efficacy	Output	Kelvin
120W	170Lm/cW	20400Lm	Tri-Colour: 3000K, 4000K & 6000K
150W	170Lm/cW	25500Lm	
200W	170Lm/cW	34000Lm	

Net Weight | 1.85kg

Options

DALI 2.0 Dimmable

Option Code

On Request



1-10V as Standard


Accessories - Plug & Play Sensors & Emergency Kit

Part Code	Description
GU-BOLT-MICRO-3PIN	Microwave Sensor
GU-BOLT-PIR-3PIN	PIR Sensor
SILVAIR-MESH-HB-SENSOR-3P	Bluetooth Sensor


Part Code	Description
GU-BOLT-MT/ST-KIT/BA	Emergency Kit




Photometric Data



60°



90°



110°

Accessories - Bracket & Reflectors

Part Code	Description
GU-BOLT-SUR-BRACKET	Surface Mount Bracket
GU-BOLT-MED/HIGH-90H	Aluminium Reflector
GU-BOLT-MED/HIGH-90PRISM	Prismatic Reflector

Dimensions

