



Helios PRO

IP67 Recessed Downlight
230mm Diameter



Technical

• Input Voltage	AC 200-240V
• Diffuser Type	Opal/Microprismatic
• Beam Spread	90°
• CRI	>85
• Power Factor	>0.9
• Typical UGR	<19
• Operating Temp.	-20 to +65°C
• Materials	Aluminium & Polycarbonate
• IP Rating	IP67
• Fire Rating	TP(a)
• Dimmable	On Request
• Lifetime	50,000 hours, L90-B10 (Ta 25°C)
• Cut Out	200mm
• Emergency Output	337Lm (TC Range) 275Lm (LG Range)

Helios Features



IP67 Ingress Protection



TP(a) Fire Rating



Back-Lit Luminaire



Tri-Colour
3000K/4000K/6000K



3 Pin Push Connector
As Standard

Helios PRO

Part Code	Power	Efficacy	Output	Kelvin
H65-PRO-WS-230TC	19W	135Lm/cW	2565Lm	Tri-Colour: 3000K, 4000K & 6000K
	21W	135Lm/cW	2835Lm	
	23W	135Lm/cW	3105Lm	
	25W	135Lm/cW	3375Lm	

Helios Pro - Low Glare Diffuser

Part Code	Power	Efficacy	Output	Kelvin
H65-PRO-WS-230TC/LG	19W	110Lm/cW	2090Lm	Tri-Colour: 3000K, 4000K & 6000K
	21W	110Lm/cW	2310Lm	
	23W	110Lm/cW	2530Lm	
	25W	110Lm/cW	2750Lm	

Net Weight | 0.9kg

Option

3 Hour Emergency
(Indicator in Bezel)

Dimming Options

Option Code

+ /EM

See Below -
Contact Office



SILVAIR CASAMBI

Accessories

Black Bezel Available

Part Code: H65-230-BEZEL-BLK




Adjustable Trim for Helios
(215mm to 245mm Cut Out)


Larger Bezel Available

Part Code: H65-ADJ-215-245-TRIM


Dimensions



Photometric Data



Opal Diffuser



Low Glare Diffuser

Energy Efficiency Rating

