



SpecLine

Architectural Linear

For Suspension &
Surface Mounting


2400mm

3000mm

Rear LED Clip-in For
Additional Uplight

Technical

• Input Voltage	AC 220-240V
• IP Rating	IP20
• Mains Frequency	50/60 Hz
• Diffuser Type	Microprismatic
• CRI	>80
• Operating Temp.	-25°C to +40°C
• Materials	Aluminium
• Dimmable	Dali Dimmable As Standard
• Emergency Output	300Lm



SpecLine Features

Microprismatic Diffuser
(Low Glare)Wattage
SwitchableDALI Dimmable
(As Standard)Tri-Colour
(3000K/4000K/5000K)

SpecLine - Black Housing

Part Code	Size	Power	Efficacy	Output	Kelvin
SPECL-WS-2400TC	2405x60x75mm	48W	120Lm/cW	5760Lm	Tri-Colour: 3000K, 4000K & 5000K
		64W	120Lm/cW	7680Lm	
		80W	120Lm/cW	9600Lm	

Net Weight | 20kg

SpecLine - White Housing

Part Code	Size	Power	Efficacy	Output	Kelvin
SPECL-WS-2400TC/WH	2405x60x75mm	48W	120Lm/cW	5760Lm	Tri-Colour: 3000K, 4000K & 5000K
		64W	120Lm/cW	7680Lm	
		80W	120Lm/cW	9600Lm	

Net Weight | 20kg

SpecLine - Black Housing

Part Code	Size	Power	Efficacy	Output	Kelvin
SPECL-WS-3000TC	3005X60X75mm	60W	120Lm/cW	7200Lm	Tri-Colour: 3000K, 4000K & 5000K
		80W	120Lm/cW	9600Lm	
		100W	120Lm/cW	12000Lm	

Net Weight | 20kg

Option	Option Code
3 Hour Emergency	+ /EM




SILVAIR CASAMBI


Indirect Accessories

Part Code:
SPECLINE-2400/UPLIGHT/WH
(White Housing)Part Code:
SPECLINE-2400/UPLIGHT
(Black Housing)Part Code:
SPECLINE-3000/UPLIGHT/WH
(White Housing)Part Code:
SPECLINE-3000/UPLIGHT
(Black Housing)

Photometric Data



Dimensions



Dimensions

